PT5RSE

TOUCH SCREEN LCD DISPLAY

Panel Type	15.0” TFT Active Matrix Panel
Max. Resolution	1024 × 768 XGA@75Hz
Pixel Pitch	0.297 (H) × 0.297 (V)
Contrast Ratio	700:1
Brightness	250 cd/m2
Display Area	304 × 228 mm
Response Time	8ms (Typ.)
Display Colors	16.2M
Viewing Angle	170°(H)/160°(V)
Signal Connector	VGA
VGA Input Signal	RGB Analog 0.7V Peak to Peak
OSD Control	Power Switch, Menu, Select (+, -), Auto
Operation Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	25 W
Power Supply	External Power Adapter
Safely & EMI	CE, FCC, TUV-GS, UL Compliant
Touch screen	Resistive; RS232
Dimension	400 x 330 x 62.8 (mm) 15.75” x 13” x 2.47”
Weight	9.7 lbs (4.4 kg)

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick NJ 08816 Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 Accuview Inc. All rights reserved.